

METHOD AND SYSTEM FOR PROVISIONING CUSTOMIZED TELECOMMUNICATIONS CIRCUITS

BACKGROUND OF THE INVENTION

5 The present invention generally relates to telecommunications circuits. In particular, the invention relates to the provisioning and linking of customized, point-to-point, dedicated circuits for use with telecommunications systems.

10 Within the telecommunications industry, there is an increasing market for customized, point-to-point dedicated circuits, or leased lines. Typically, these circuits are "provisioned" via transport suppliers to provide the requested point-to-point service. "Provisioning" conventionally refers to the supplying of telecommunications service to a user, and may include the assignment of transmission, equipment, switching, wiring and bandwidth to the customer associated with that service. For example, a customized circuit
15 may provide dedicated communications bandwidth between a customer's facilities in two different cities. These circuits have traditionally been provisioned by one of the many transport suppliers in the telecommunications industry. Each transport supplier generally has its own network over which dedicated circuits may be provisioned.

20 There are limitations, however, to a transport supplier's ability to provision circuits on its own network. First, most suppliers' networks are limited geographically. Because it is expensive to build and maintain large networks, few suppliers are able to maintain networks that serve a large number of locations. In addition, networks have limited capacity. Once
25 capacity is reached for a given segment of a supplier's network, additional circuits must be routed around that segment. Finally, different types of suppliers maintain different types of networks. For instance, different suppliers serve various local, regional, national, and global markets. A national supplier maintains long-distance circuits, but might not be able to
30 provide a local connection to a customer's facility. Likewise, a local supplier may not have access to the long-distance circuits required by a given

customer or end-user. Furthermore, the control of entire circuits by a single supplier may result in increased costs for customers of the circuits.

For these reasons, transport suppliers often provision portions of circuits "off-network." This requires a first supplier to negotiate with a second supplier to obtain access to the second supplier's network. If the two suppliers are competitors, the negotiations can be difficult and inefficient. The result is that the customer may pay more and wait longer than should be necessary to obtain access to a dedicated circuit. Moreover, provisioning portions of a circuit off-network requires interconnection of the network segments of at least two different transport suppliers. This often involves physical connection of the circuit from one facility to another, which can result in additional delays.

Telecommunications customers may also suffer from a lack of information about internal operations within the industry or with a particular transport supplier. In addition, the somewhat esoteric properties of the provisioning process itself may be difficult to discern. For instance, the complex process of provisioning a circuit typically includes meeting a number of "critical dates," or deadlines, within the process before the circuit can be operational. If the customer is unaware of the scheduling process, a critical date can be missed. The result is often a delay in provisioning the circuit or the loss of the opportunity to provision the circuit. However, if the customer is aware of the provisioning schedule, the customer is in a better position to monitor the transport supplier and ensure that the circuit is provisioned on time. There are other details of the provisioning process, such as real-time availability, capacity, and pricing of particular network segments, that, if known to the customer, could help ensure that the customer gets the best available circuit and that the circuit is provisioned on schedule. Customers generally are not aware of these provisioning details, however, because suppliers usually do not share them with customers.

It is therefore an object of this invention to provide customers with updated network parameter information from a variety of transport suppliers.

It is a further object of this invention to provide an improved method and system for provisioning customized circuits wherein customers are able to conveniently order and obtain access to circuits involving the networks of a variety of transport suppliers.

5 It is another object of this invention to provide an improved method and system for provisioning customized circuits wherein multiple network segments from various transport providers may be linked via neutral exchange facilities.

10 It is yet another object of this invention to provide an improved method and system for provisioning customized circuits wherein multiple network segments from various transport providers may be provisioned and linked according to an automated process in response to a specific order.

BRIEF SUMMARY OF THE PREFERRED EMBODIMENTS

15 In accordance with the present invention, a method and system are described for provisioning customized, dedicated point-to-point circuits. According to one aspect of the invention, a method relates to a facilitator that provisions the circuit and then provides a customer/end-user with access to the circuit. The method includes the step of receiving a customer request for a circuit between at least two terminal points. Network parameters related to the customer request are then evaluated, after which a plurality of network segments from separate transport suppliers are linked. The network segments may be linked via facilitator-controlled exchange facilities to form a provisioned circuit between the customer-specified terminal points. Access to the circuit is then provided to the customer.

25 According to another aspect of the invention, a method of obtaining a provisioned circuit between at least two terminal points is described. The method includes the step of requesting from a facilitator a circuit between the terminal points. At least one circuit option is then received from the facilitator in accordance with the request. Each circuit option includes a plurality of network segments from separate transport suppliers, wherein the network segments may be linked via at least one facilitator-controlled exchange

30

facility to form a complete circuit. One of the circuit options is then selected to be a provisioned circuit, and access to the provisioned circuit is then received.

According to yet another aspect of the invention, a system for provisioning a circuit between at least two terminal points is described. The system includes at least one processing server serving a plurality of customers. A database resides on the processing server. The database is updated on a regular basis with information related to a plurality of network segments of various transport suppliers. The information is received from the plurality of transport suppliers. A plurality of exchange facilities are provided, in communication with at least one of the servers to assist in the linking of network segments. Logic software also resides on the server. The logic software is in communication with the database and the exchange facilities to automate the linking of the network segments via the exchange facilities to form a provisioned circuit in accordance with a customer request.

The invention provides several advantages over known methods and systems. Customers are provided with network parameter information for network segments maintained by different transport suppliers. This information may be updated on a real-time basis. End-users are thus able to conveniently order and obtain access to circuits involving the networks of a variety of transport suppliers. Individual network segments comprising a customized circuit are linked via neutral exchange facilities. Moreover, the linking of network segments from different transport suppliers may be performed automatically in response to a customer order.

The invention and its various advantages will become more apparent to those skilled in the art from the ensuing detailed description of preferred embodiments, reference being made to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The subsequent description of the preferred embodiments of the present invention refers to the attached drawings, wherein:

FIG. 1 is a block diagram of a typical point-to-point circuit connecting a customer's facilities in Los Angeles and New York City;

FIG. 2 is a block diagram of a system for provisioning customized circuits according to one presently preferred embodiment of the invention;

FIG. 3 is a block diagram of an information exchange according to another presently preferred embodiment of the invention;

5 **FIG. 4** is a flow diagram depicting a method of provisioning a customized circuit according to yet another presently preferred embodiment of the invention;

10 **FIG. 5** is a block diagram of an exemplary provisioned circuit between end-user facilities in Los Angeles and New York City according to still another presently preferred embodiment of the invention; and

FIG. 6 is a flow diagram depicting a method of ordering a customized circuit according to a further presently preferred embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 Referring now to the accompanying drawings, **FIG. 1** shows the components of a typical dedicated point-to-point telecommunications circuit **100**. The circuit **100** comprises a plurality of network segments **102a-d**. Each network segment **102 a-d** is a portion of a transport supplier's network that connects two points on the network, and may be linked with other network segments to form a point-to-point circuit between desired destinations. For instance, a national transport supplier may maintain a network segment **102b** between Los Angeles and Chicago, and another network segment **102c** between Chicago and New York City. These network segments **102b,c** may be linked together to form a single circuit between Los Angeles and New York City.

25 National transport suppliers typically do not maintain local networks in every city. Instead, the long-distance network segments maintained by a national transport supplier terminate in one or more centralized interconnection facilities **104a-c** within a city. Accordingly, if a customer wants a dedicated circuit from its particular location **A** in Los Angeles to a location **Z** in New York City, local network segments **102a, d** are used to provide a localized connection between the termination points of the long-

30

distance segments **102b, c** and the particular customer locations **A,Z**. For instance, the local segment **102a** provides a connection between the customer location **A** in Los Angeles and the termination point of the long-distance segment **102b**. Likewise, local segment **102d** provides a connection between the customer location **Z** in New York City and the termination point of the long-distance segment **102c**. The requested circuit from location **A** to location **Z** is thus formed via the connection of four network segments **102a-d**.

Depending upon the location of the customer's facilities, there may be more than one local network segment **102a,d** at each end of the circuit **100**. Multiple local network segments **102a,d** may be required to extend the circuit **100** to the customer's facilities. For instance, if the local transport supplier that provides the a necessary local network segment **102a** can only provide a connection to the customer's building, but not to the customer's facilities within that building, an additional network segment may be required. This "building riser" network segment (not shown) extends within the building from the local transport supplier's connection to the customer's facilities.

As discussed above, the local network segments **102a,d** typically are not provided by the same transport suppliers as the long-distance network segments **102b,c**. As a result, the network segments **102a-d** combined to form a single point-to-point circuit **100** often are maintained by more than one transport supplier. A first transport supplier may provide the local network segment **102a** in Los Angeles, and a second transport supplier may provide the local network segment **102d** in New York City. A third supplier may then provide the long-distance network segments **102b,c**. In fact, each of the two long-distance network segments **102c** also may be provided by a different transport supplier, depending upon the scope and availability of each transport supplier's network. As a result, up to four different transport suppliers may be responsible for providing the network segments **102a-d** that form the customer's circuit **100** in **FIG 1**.

Connections between network segments **102** maintained by different transport suppliers are created at the interconnection facilities **104 a-c**. Typically, one transport supplier "co-locates" connection equipment at the

interconnection facility of another transport supplier by leasing space for the equipment in the facility. Connection of one segment to another is accomplished by physically connecting the equipment of one supplier to that of another or by programming a control system to logically connect the network segments within the interconnection facility. If a customized circuit requires connection of network segments from two different transport suppliers that do not maintain co-located equipment, a connection must be constructed by running a new network segment between the interconnection facilities of the two transport suppliers.

The provisioning of circuits involving multiple transport suppliers as herein described can result in excessive costs and inefficiencies to the customer or end-user. Moreover, the central interconnection facilities **104a-c** are each typically controlled by a separate transport supplier, and many transport suppliers are reluctant to grant their competitors access to proprietary interconnection facilities **104a-d** for purposes of linking network segments **102a-d**. Accordingly, if the customer orders the entire circuit **100** through a single transport supplier, that transport supplier must negotiate with the other transport suppliers to provision segments of the circuit **100** "off-network" and to gain access to specific connection facilities **104**. These negotiations may be difficult and inefficient. Alternatively, the customer may order each network segment **102** directly from the relevant transport supplier. It is the customer that then must negotiate with the transport suppliers to ensure that the network segments **102** are properly interconnected. Either way, the customer usually must interface with all four transport suppliers to pay for and maintain the customized circuit **100**.

According to at least one embodiment of the present invention, an information exchange is provided to reduce the inefficiencies of provisioning a point-to-point circuit, and to provide a single resource for ordering and maintaining the circuit. The information exchange is part of a system for provisioning customized dedicated point-to-point circuits.

FIG. 2 shows a first embodiment of a circuit provisioning system, designated generally by the numeral **200**, according to this invention. An

information exchange **202** is provided which includes a proprietary database **204** containing various types of information related to the provisioning of circuits. The information exchange **202** acts as a processing server to serve customers in response to requests and orders. Depending upon system requirements, the database **204** may actually consist of a plurality of interconnected databases **204a-d**, as shown in **FIG. 3**. For instance, separate databases **204a-d** may be maintained to track network parameter information, quote information, customer information, and billing information. The network parameter information contained in the database **204** may include information relating to capacity, availability, physical location, and pricing information from a variety of transport suppliers. Preferably, network parameter information is maintained for a plurality of individual network segments **102** available from the transport suppliers. This facilitates evaluation of network parameters on a per-segment basis.

Network parameter information for a given network segment **102** is preferably obtained from the transport supplier that maintains the network segment **102**. Preferably, the database **204** is updated frequently to provide the most recent information possible. Most preferably, the information exchange is connected directly to the databases of transport suppliers such that the database **204** of the information exchange **202** is updated instantly when a supplier's database is updated. In this case, the information exchange **204** provides real-time data on network parameters.

The information exchange **202** is preferably maintained by a facilitator **250** that is able to interface directly with transport suppliers to obtain network parameter information and to arrange for circuit provisioning. The facilitator **250** may be an agent that orders network segments **102** and circuits 100 from transport suppliers on behalf of a customer. However, it is important to note that the facilitator may also be other than a mere agent. The facilitator may act as principle in both the buying and selling of circuits. For example, the facilitator is the party of record in all service agreements with transport suppliers. The facilitator may then sell the circuits to its own customers, who become the "end-users" of the circuits. According to this embodiment, the

end-users gain the advantage of being anonymous to the transport suppliers providing the network segments that make up the circuit. Another advantage gained when the facilitator 250 acts as the buyer of record in all transactions with transport suppliers comes from the economics of scale. The facilitator is able to negotiate more competitive rates by committing to purchase a large fixed amount of network access from particular transport suppliers. The savings in cost may then be passed on to the end-user, resulting in less expensive circuits for the facilitator's customers.

It is also important to note that the facilitator **250** need not necessarily be one person. The facilitator may be several persons within a single entity or several entities, or a corporate entity itself. Furthermore, the facilitator may also comprise an automated or intelligent system or software program configured to interface with transport suppliers and customers.

The information exchange **202** also enables the facilitator **250** to provide customers with a single point of contact for the provisioning, installation, and maintenance of circuits from multiple transport suppliers, as well as circuit access and network management.

The information exchange **202** includes an interface system **206** to facilitate communications by the facilitator 250 with customers and transport suppliers. The interface system **206** is preferably linked to an automated ordering and provisioning system **208**, which in turn is linked to the information exchange database **204**. The interface system **206** facilitates communication with transport suppliers in a number of ways. Preferably, a direct connection **212** is provided between a transport supplier **210a** and the information exchange interface **206**. Alternatively, a transport supplier **210b** may connect to the information exchange interface **206** via the Internet **214**. In this case, the connection via the Internet **214** is preferably secure. A transport supplier **210c** may also connect to the information exchange interface **206** via a standard public switched telephone network (PSTN) connection **216**. For instance, communications between the transport supplier **210c** and the information exchange interface **206** via a PSTN connection may take the form of data, facsimile, voice, or a combination

thereof. In the case of facsimile and voice communications, the facilitator **250** that maintains the information exchange facilitates the communication.

Through these various forms of communication with transport suppliers, the facilitator **250** and the information exchange interface **206** are able to update the information exchange database to represent current network parameter information. The facilitator **250** and the information exchange **202** are also able to place orders with transport suppliers **210** for access to particular network segments **102**. During the provisioning and installation process, the facilitator **250** and the information exchange **202** are able to monitor the progress of the transport suppliers to ensure that no critical dates are missed and that the circuit is available to the customer on schedule. When the provisioning process is complete, the facilitator is then able to monitor and maintain the circuit on behalf of the customer.

This system eliminates the inefficiencies of traditional circuit provisioning in a number of ways. First, the facilitator **250** is able to order circuits directly from a wide variety of transport suppliers. The information contained in the information exchange database **204** allows the facilitator to offer customers many or all of the available circuit options from the various transport suppliers. For example, a customer may choose to order different network segments **102** of a circuit **100** from different transport suppliers. The customer may compare a variety of network parameters, such as price, capacity, and availability, for various circuit segments by consulting the information exchange database **204**. The customer may then choose the best circuit option based on these parameters. Alternatively, the facilitator **250** may filter the available options based on predetermined customer preferences and provide only the one or more options that most closely match those preferences.

The information exchange **202** also eliminates inefficiency by providing the facilitator **250** with information regarding the provisioning and scheduling processes of various transport suppliers. Each transport supplier has its own set of operating procedures by which circuits are provisioned. These procedures typically include a series of critical dates that occur during the

provisioning process. If certain necessary events do not occur before a critical date, the entire provisioning schedule may be delayed. The delays can be substantial, and can result in excessive costs to the customer. Because the customer is typically not aware of pending critical dates in the provisioning process, the customer may not realize that the process is behind schedule before additional costs are incurred. By maintaining information regarding the scheduling and operating procedures for each transport supplier in the information exchange, **202** the facilitator **250** is able to monitor the provisioning process and to anticipate critical dates. The facilitator **250** may then take affirmative action to ensure that each critical date in the provisioning process is met. The facilitator thereby ensures a more dependable and predictable provisioning process.

The interface system **206** of the information exchange **202** also facilitates communication with customers in a number of ways. For instance, a direct connection **218** may be provided between a customer **220a** and the information exchange interface **206**. Alternatively, a customer **220b** may access the information exchange interface **206** via the Internet **214**. In this case, the connection via the Internet **214** is preferably secure. A customer **220c** may also connect to the information exchange interface **206** via a PSTN connection **222**. For instance, communications between the customer **220c** and the information exchange interface **206** via a PSTN connection may take the form of data, facsimile, or voice. In the case of facsimile and voice communications, the facilitator that maintains the information exchange facilitates the communication.

Communications with customers via the information exchange **202** include providing a customer with network parameter information relating to a number of available circuit options connecting network segments **102** from a variety of transport suppliers, and receiving customer orders for customized circuits. The facilitator **250** may also provide the customer with quotes or estimated pricing before an order is received. The information exchange **202** may also offer a customer with single-point network management services for provisioned circuits.

The process of provisioning a circuit according to a preferred embodiment of this invention will now be discussed with reference to the flow chart of **FIG. 4**. One or more individual steps of the method may be performed automatically by the interface system **206** and the automated ordering and provisioning system **208** in connection with the information exchange database **204**. First, the facilitator **250** receives a request for a customized circuit from a customer in step **402**. The customer order is preferably received via the interface system **206** and the automated ordering and provisioning system **208** of the information exchange **202**. In the order, the customer may specify certain network parameters such as the terminal points of the circuit, preferred capacity, particular routing information, and the date by which the customer needs access to the circuit. The preferred capacity may be, for example, particular digital service or optical carrier levels such as DS-1, DS-3, OC-3, OC-12, OC-48, OR OC-192. The customer may also specify preferred transport suppliers, as well as particular circuit features such as fiber/copper, redundant/non-redundant, SONET/non-SONET, and protected/non-protected.

After receiving the customer's order, the facilitator **250** evaluates the network parameters of available network segments **102** that might be combined to fulfill the customer's order (step **404**). This may be done by consulting the network parameter information contained in the information exchange database **204**, a computer interface display **260** or other suitable display means. Optionally, the facilitator **250** may provide the customer with further network parameter options in step **406**. Based on the results of the evaluation and any response received from the customer, the facilitator **250** identifies the customized circuit options that are available to fulfill the customer's order in step **408**. The available circuit options may offer different routing options, as well as different combinations of network segments **102** from various transport suppliers. Circuit options may also vary by price and scheduling availability. In step **410**, the facilitator **250** optionally may then filter the available circuit options to identify those circuit options that most closely match the customer's request. The facilitator **250** then provides a list

of circuit options to the customer in step **412**, and receives the customer's circuit selection in step **414**.

The customer's circuit selection indicates to the facilitator **250** which network segments **102** from which transport suppliers the customer would like to use. Based on this information, the facilitator **250** orders provisioning of the proper network segments **102** from their respective transport suppliers in step **416**. As described above, the facilitator **250** as an entity becomes the party of record with respect to all service agreements with the transport suppliers. Accordingly, the end-user may remain anonymous to the transport suppliers that supply the network segments of the provisioned circuit. During the provisioning process, the facilitator **250** optionally may monitor the progress of the transport suppliers in step **418** to ensure that no critical dates are missed and that the customer's circuit will be provisioned on schedule. After the transport suppliers have provisioned each network segment, the facilitator links the terminal points of the proper network segments **102** together to form the circuit in step **420**. The facilitator may itself link the terminal points of the network segments via facilitator-controlled exchange facilities. Alternatively, the facilitator may request that one or more transport suppliers provide the link between network segments. Either way, the facilitator then provides the customer with access to the provisioned circuit in step **422**. Thereafter, the facilitator serves as a single point of contact for the customer in connection with all billing and circuit maintenance procedures relating to each of the network segments **102** of the provisioned circuit.

The linking of network segments **102** may be accomplished via facilitator-controlled exchange facilities **502** as shown in **FIG. 5**. The exchange facilities **502** are facilities that provide interconnection points between multiple transport suppliers. These facilities **502** are preferably transport supplier-neutral, in that they are controlled by the facilitator rather than any particular transport provider. The neutral nature of the exchange facilities helps to prevent the competitive tensions typically encountered when one transport supplier connects a network segment **102** to that of another

transport supplier via co-location of equipment at the second supplier's interconnection facility **104**.

To link multiple network segments **102** together via facilitator-controlled exchange facilities to form a provisioned circuit **500**, the facilitator first orders
5 access to the proper segments **102** from their respective transport suppliers. The facilitator communicates orders to the transport suppliers via the information exchange **102** as described with respect to **FIG. 2**. In placing an order, the facilitator requests that each segment terminate at a facilitator-controlled exchange terminal **502**. At each exchange terminal **502**, the
10 facilitator links two or more network segments **102** together. Foreexample, **FIG. 5** shows an exemplary customized circuit between customer locations in Los Angeles and New York according to this embodiment of the invention. Four network segments **102a-d** are connected to form the circuit, similar to those shown in **FIG. 1**. However, according to this embodiment of the invention, the network segments are linked via facilitator-controlled exchange facilities **502a-c**. Because the facilitator, rather than a transport supplier, links the network segments **102a-d** together, the various transport suppliers may be unaware of how their network segments are connected. As a result, a given transport supplier may not know if its network segment **102** is
15 connected to the network of a rival transport supplier. Moreover, because the facilitator controls each exchange terminal **502**, it is the facilitator, rather than any given transport supplier, that sets the terms surrounding the use of the exchange facility. Accordingly, the tensions and inefficiencies of using different network segments **102** from competing transport suppliers are substantially or completely alleviated with respect to this provisioning operation.
20
25

The process of ordering a circuit according to a preferred embodiment of this invention will now be discussed with reference to the flow chart of **FIG. 6**. In step **602**, the customer orders a circuit from the facilitator.
30 Preferably, this step **602** is accomplished via the interface system **206** and automated ordering and provisioning system **208** of the information exchange **202**, as described with respect to **FIG. 2**. The customer may also specify

certain preferred network parameters as shown by step **604**. For instance, the customer may specify the terminal points of the circuit, a preferred network capacity such as DS-1 or OC-3, particular preferred routing information, and the date by which the customer needs access to the circuit.

5 The customer may also specify preferred transport suppliers, as well as particular circuit features such as fiber/copper, redundant/non-redundant, SONET/non-SONET, and protected/non-protected. Based upon this information, the facilitator evaluates network parameter information associated with available network segments **102** to identify available circuit options. In doing so, the facilitator may consult the information exchange database **204**. The facilitator may also filter the available circuit options to identify particular preferred circuit options that most closely match the customer's preferences.

10 The customer then receives one or more circuit options from the facilitator in step **606**. Each circuit option consists of one or more network segments **102** linked together to form the complete circuit. The network segments **102** included in a particular circuit option may be from different transport providers. As described above, the network segments **102** may be linked together via facilitator-controlled exchange facilities **502**, as described with respect to **FIG. 5**. In step **608**, the customer selects one of the circuit options and communicates the selection to the facilitator via the information exchange **202**. After the facilitator has provisioned the circuit by ordering the necessary network segments **102** from the proper transport suppliers, and by linking those network segments **102**, the customer receives access to the provisioned circuit in step **610**. Thereafter, the customer interfaces with the facilitator as a single point of contact for all billing and circuit maintenance procedures relating to each of the network segments **102** of the provisioned circuit **500**.

25 The implementation of the various software and logic protocols necessary for operation of the present embodiments may be done through conventional means known in the art. For example, if the facilitator **250** is implemented as a software program running on a server or other system,

FIG. 5

such program may be written in a variety of high-level or low-level computer languages. The software may run on any hardware system capable of running the software and interfacing as necessary with the switching networks and other telecommunications networks described. Furthermore, the particular interfaces are known in the art, and can include relays, DSLAM interfaces, or other converters in either software or hardware form that can translate actions by the facilitator **250**, interface **206**, or other components with other components either outside or inside the system.

The invention has been described in detail with particular reference to preferred embodiments thereof and illustrative examples, but it will be understood that variations and modifications can be effected within the spirit and scope of the invention.